

1200°C Box Furnace

Temperature uniformity and fast heat-up, and recovery and cool-down rates are excellent benefits of our 1200°C Box Furnace. It has a dense load capability and the spring-loaded door assures secure closure.



Features

- Double shell construction
- Individual heating elements at chamber top, bottom, and sides
- Moldatherm® ceramic fiber insulation
- High temperature insulation in vestibule plug door
- Heating element embedded Moldatherm® pads

- Refractory plate heating unit for Model BF51442C
- Plantinel® II thermocouple with 10 compensated lead wire and polarized plug
- Temperature - 1200°C (2192°F) Maximum
- Chamber Sizes - 551.25 Cubic Inches - 28.24 Cubic Feet

Options

- Built-In Temperature Control Console
 - Provides additional features and versatility for your control system
- Programmable temperature control (Option P)
 - Offers flexibility of ramping to multiple setpoint levels and holding for variable time periods at those levels
 - Provides up to four 16-programmable segments or one 64 segment program
- Excess temperature protection (Option B)
 - Provides positive protection of both furnace and load in the event of failure in the primary control circuit

- Ethernet communications available
- Atmosphere Retorts
 - Available for all Lindberg/MPH 1200°C box furnaces when controlled atmosphere processing is required
 - Atmosphere Control Consoles

Model	Chamber Dimensions W x H x D in. (cm)	Outer Dimensions W x H x D in. (cm)	Wattage	Shipping Weight (lbs.)	Control Console Model No.
51442	7.5 x 5.25 x 14 (19.1 x 13.3 x 35.6)	20 x 20 x 24.5 (50.8 x 50.8 x 62.2)	4,880	135	58114
51542	10.5 x 9.5 x 14.5 (26.7 x 24.1 x 36.8)	28 x 28.5 x 31 (71.1 x 72.4 x 78.7)	6,200	320	58114
51642	13 x 8 x 15 (33 x 20.3 x 38.1)	30 x 27 x 32 (76.2 x 68.6 x 81.3)	6,800	380	58124
51662	12 x 12 x 14 (30.5 x 30.5 x 35.6)	30 x 31 x 31 (76.2 x 78.7 x 78.7)	6,800	450	58124
51668	12 x 12 x 24 (30.5 x 30.5 x 61)	30 x 31 x 41 (76.2 x 78.7 x 104.1)	12,000	600	58124
51862	14 x 16 x 24 (35.6 x 40.6 x 61)	34 x 35 x 41 (86.4 x 88.9 x 104.1)	16,000	800	58174

Model	Preset TC Input	Preset Control Range	Maximum Current / Zone	Voltage	Hertz	Overall Size HxWxD in inches (cm)	Shipping Weight lbs.
58114	Platinel II	1-1200°C	30 Amps	208/240	50/60	10 x 14 x 19 (25.4 x 35.6 x 48.3)	30
58124	Platinel II	0-1200°C	60 Amps	208/240	50/60	10 x 14 x 19 (25.4 x 35.6 x 48.3)	50
58174	Platinel II	0-1200°C	120 Amps	208/240	50/60	17 x 17 x 21 (43.2 x 43.2 x 53.3)	30

All specifications are subject to change without notice.



Lindberg/MPH
Phone: (269) 849-2700

P.O. Box 131, 3827 Riverside Road Riverside, MI 49084
 • Fax: (269) 849-3021 • lindbergmpf@lindbergmpf.com
www.lindbergmpf.com